



T and S Series Single Phase Solar GTI

1KW/1.5KW/2.2KW/3.0KW/3.6KW/4.4KW/5.0KW/6.0KW



Big LCD display



Power export limit



Compact and easy to install



Wifi/GPRS/Lan communication optional



Simpler

Quick and easy single person installation
Fault codes warning view on LCD display
Built-in limiter optional



Safer

comply with international quality standards
tested by TÜV, BV, Dekra etc.



Great reliability

IP65 ingress protection
10+years R&D accumulation and support

ANYTIME, ANYWHERE

REMOTE MONITORING PLATFORM

Monitor system performance in real-time via smartphone app or web portal using our advanced monitoring platform.

S Series Single Phase



SOLAR GRID TIED INVERTER

Technology Data



Model No	T1000TL	T1500TL	T2200TL	T3000TL	S3600TL	S4400TL	S5000TL	S6000TL
DC Side / Input Parameters								
Max DC power (W)	1500	2250	3300	4500	5400	6600	7500	7800
Max DC voltage (Vdc)	500	500	500	500	500	500	500	500
Min System start/Shut down voltage (Vdc)	75/80	75/100	75/100	75/100	75/100	75/100	75/100	75/100
MPPT voltage range(Vdc)	80~450	100~450	100~450	100~450	100~450	100~450	100~450	100~450
Max. input current (A)			18				20	
Number of MPP trackers	1	1	1	1	2	2	2	2
Strings per MPP tracker	1	1	1	1	1	1	1	1
AC Side / Output Parameters								
Nominal output power (W)	1000	1500	2200	3000	3300	4000	4600	5500
Maximum output power (W)	1100	1650	2420	3300	3680	4400	5000	6000
Nominal output voltage/range (V)	208,220,230,240/180~270							
AC grid frequency/range (Hz)	50Hz,60Hz(auto-selection) / 44Hz-55Hz; 54Hz-65Hz							
Maximum output current (A)	6	8	12	16	16	21	23	26
AC connection (with PE)	Single phase							
Current distortion(THDi)	<1.5%	<1.5%	<1.5%	<1.5%	<2.5%	<2.5%	<2.5%	<2.5%
Power factor	~1%(Adjustable from 0.8 leading to 0.8 lagging)							
Efficiency								
Maximum conversion efficiency	97.3%	97.3%	97.4%	97.5%	97.8%	97.8%	97.5%	97.6%
European efficiency	97.0%	97.0%	97.1%	97.2%	97.3%	97.3%	97.2%	97.3%
MPPT efficiency	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%
Safety and Protection								
DC reverse-polarity protection	yes							
Anti-islanding / Overvoltage protection	yes							
Short circuit protection	yes							
Leakage current protection	yes							
Grid monitoring / Ground fault monitoring	yes							
DC/AC side SPD(thermally protected)	yes							
General Parameters								
Dimension (L/W/H)(mm)	350/305/110				350/315/125			
Weight (kg)	5				8			
Embedded DC Switch	Optional							
Night power consumption (W)	< 0.2							
Isolation type	Transformerless							
Protection degree	IP65 according to IEC60529							
Operation temperature (°C)	-25 ~ +60							
Cooling concept	Natural convection							
Operatiing Altitude (m)	<2000m without power derating							
Acoustic noise level (dB)	< 25							
Display	Graphic LCD							
Communication Interface	Standard WIFI; RS485 (optional)							
Warranty	5 years; 5/7/10 years for optional							
Certificates and Approvals								
CE-(EMC/LVD) : EN(IEC) 61000-1/-2/-3/; EN(IEC) 62109-1/-2								